



The GENEPI-3C accelerator for the GUINEVERE project

M.Baylac¹, H.Ait Abderrahim², P.Baeten², P.B.Bard¹, A.Billebaud¹, G.Bergmans², P.Boge¹, D.Bondoux¹, J.Bouvier¹, T.Cabanel¹, P.Desrues⁴, Y.Carcagno¹, G.Dargaud¹, JM. De Conto¹, E.Froidefond¹, G.Gaudiot⁵, JM.Gautier^{4†}, Y. Gómez Martínez¹, G.Granget⁶, G.Heitz⁵, M.Heusch¹, B.Laune³, D.Marchand¹, F.Mellier⁶, Y.Merrer⁴, R.Micoud¹, E.Perbet¹, M.Planet¹, P.Poussot⁵, D.Reybet³, C.Ruescas⁵, J.P.Scordillas¹, D.Tourrè¹, F.Vermeersch², G.Vittiglio²

¹ LPSC, UJF/CNRS-IN2P3/INPG, Grenoble, France, ² SCK-CEN, Mol, Belgium, ³ IPNO, CNRS-IN2P3/UPS, Orsay, France, ⁴ LPC Caen, ENSICAEN/Université de Caen/CNRS-IN2P3, Caen, France ⁵ IPHC-DRS/ULP/CNRS-IN2P3, Strasbourg, France, ⁶ CEA, Cadarache, France.

The GUINEVERE project

Generator of Uninterrupted Intense NEutrons at the lead VEnus Reactor


- Part of the Program IP-EUROTRANS (FP6), DM2 ECATS
- Provide an system representing an ADS demonstrator, continuing the MUSE-4 experimental program (FP5)
- Investigate on-line reactivity monitoring, sub-criticality determination & operational procedures in an ADS
- Collaboration CNRS/IN2P3 (France), SCK-CEN (Belgium) & CEA (France)
- Zero(low)- power coupling of
 - a fast lead core reactor, VENUS-F
 - a neutron source, GENEPI-3C

GUINEVERE's keypoints

- Improving from MUSE4/GENEPI-1, new specifications
 - Vertical coupling
 - Neutron source operated in both pulsed and continuous modes
- Reactor (SCK-CEN) : VENUS-F**
 - Modify the water-moderated VENUS into a solid lead core
 - Fuel and lead rods provided by CEA-Cadarache
 - Adapt building to accomodate the accelerator above the reactor
- Construction of a new neutron source (CNRS/IN2P3) : GENEPI-3C**
 - Vertical beamline insertion into the core
 - Pulsed mode
 - Continuous mode with programmable beam interruptions

VENUS-F

- Fast core based on metallic Uranium (30% enrichment) & solid lead
- Sub-critical configurations with central insertion channel




VENUS-F core (top view)



VENUS-F reactor

- Construction of additional floor to host the accelerator

Accelerator design



GENEPI-3C coupled to VENUS-F



Partial GENEPI-3C assembly at LPSC

GENEPI-3C beam specifications

- Generator of Neutrons Pulsed & Intense
 - Electrostatic Deuteron accelerator (240 keV)
 - Neutron (14 MeV) production via $T(d,n)4He$
- Accelerator capable of producing alternatively
 - Intense pulsed mode
 - 40 mA peak current
 - $FWHM < 1 \mu s$
 - repetition rate : 10-5000 Hz
 - Continuous mode
 - DC beam
 - programmable beam trips
- Deuteron ion source driving the beam structure


Mean current	160 μA to 1 mA
Beam trip rate	0.1 to 100 Hz
Beam trip duration	$\sim 20 \mu s$ to 10 ms
Transition edge	$\sim 1 \mu s$
Beam spot size	$\Phi \sim 20-40$ mm
Maximum n rate	$\sim 5 \times 10^{10}$ n/s
Pulse stability	$\sim 1\%$

Ion source

- Ion source to generate D+ beam
 - Duoplasmatron source
 - Well adapted for pulsed mode
 - Beam extracted & focused by a series of 5 electrodes (up to 60 kV)
- Ion source** (image)
- R&D on test bench to reach DC mode requirements
 - ✓ 1 mA D+
 - ✓ beam interruptions
 - ✓ transitions ON/OFF $\sim \mu s$
 - ✓ adjustable trip rate : under study


Target

- Thin layer of TiT (12 Ci) deposited over a copper disk
- Current and temperature to be measured at back of target
- Temperature to be kept below 100 ° Celsius (T desorption)
- Cooling by air only (250 W beam power) in a non-cooled core ($\sim 45^\circ$)
- Mounted on beamline termination (thimble)
- Silicon detector at thimble front-end to monitor α recoil particles




Beam line insertion

- Target within the thimble to be inserted at core center
- Machine sections mobile for periodic target changes & core maintenance
 - Dipole magnet to grant access to the vertical line
 - Vertical beamline to be lifted up
- Vertical line & shielding embedded in support structure, guided at upper and lower level.



Dipole magnet

- Deflect the beam towards core & perform magnetic separation
- Magnet features : C design, 0.5 m radius, 0.2 T, 30° faces
- Water cooled with stringent precautions against leaks
 - Coil & cooling system waterproof
 - Water & electrical connections in waterproof casing
 - Multiple leak detection
- Ion collector connected to the chamber (D2+, D3+ out of source)
- Proton recoil telescope facing the target



Milestones

- R&D remains on source : DC mode & current driving for coupling
- Machine assembly & commissioning at LPSC underway
 - Half of the machine tested & validated (March 2009)
- First beam at LPSC (220 keV, 500 Hz) (image)
- Assembly & commissioning (LPSC) : until summer 2009
- Machine assembly & tests (SCK-CEN) : September-October 2009
- Load VENUS & start physics program : November-December 2009

This work is partially supported by the 6th Framework Program of the European Commission (EURATOM) through the EUROTRANS Integrated Project contract # FI6W-CT-2005-516520, and the French PACEN program of CNRS.